




+


### PLAN OF MODULAR EXPANSION JOINT SEAL - LEFT SIDE

ASSEMBLED BY : CHECKED BY :		DATE : DATE :	
DRAWN BY : EEM CHECKED BY : VAP	7/96 7/96	REV. 10/1/11 REV. 6/13 REV. 12/17	MAA/GM MAA/GM MAA/THC

# **COVER PLATE DETAILS**









LIMITS OF MODULAR EXPANSION JOINT SEAL 2" MIN. 5" MIN. BLOCKOUT - BLOCKOUT SKETCH SHOWING LIMITS OF MODULAR EXPANSION JOINT SEAL-BARRIER RAIL - CLOSED-END FERRULE PROJECT NO.\_ ELEVATION COUNTY STATION:\_ **CONCRETE INSERT** \* \* EACH WELDED ATTACHMENT OF WIRE TO FERRULE SHALL SHEET \_ OF DEVELOP THE TENSILE STRENGTH OF THE WIRE. STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH STANDARD MODULAR EXPANSION JOINT SEAL DETAILS FOR BARRIER RAIL SHEET NO. REVISIONS NO. DATE: DATE: BY: BY: DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED TOTAL SHEETS

# PLAN OF MODULAR EXPANSION JOINT SEAL - RIGHT SIDE

### NOTES

FOR MODULAR EXPANSION JOINT SEALS, SEE SPECIAL PROVISIONS.

THE STEEL PLATES SHALL CONFORM TO AASHTO M270 GRADE 36 OR APPROVED EQUAL AND BE PAINTED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS. AT THE CONTRACTOR'S OPTION, THE PLATES MAY BE METALLIZED AFTER FABRICATION. SEE SPECIAL PROVISIONS FOR THERMAL SPRAYED COATINGS (METALLIZATION).

THE  $\frac{3}{4}$ "  $\varnothing$  HEX HEAD BOLTS SHALL CONFORM TO ASTM F593 ALLOY 304 STAINLESS STEEL.

THE <sup>3</sup>/<sub>4</sub>" CONCRETE INSERTS SHALL BE CLOSED-END FERRULES WITH LOOPED WIRE STRUTS ATTACHED TO THEM. THE INSERTS SHALL CONFORM TO AASHTO M169, GRADE 12L14 AND SHALL HAVE A TENSILE WORKING LOAD CAPACITY OF 3000 LBS.

NO SEPARATE PAYMENT WILL BE MADE FOR FURNISHING AND INSTALLING THE COVER PLATE. THE ENTIRE COST OF THIS WORK SHALL BE INCLUDED IN THE LUMP SUM PRICE FOR "MODULAR EXPANSION JOINT SEALS".

	SKEW ANGLE	TOTAL MOVEMENT ALONG À ROADWAY
END BENT #1		
BENT #1		
END BENT #2		

STD. NO. MEJS1