

SKEW LIMITS			
	GIRDER SIZE	GIRDER SPACING *	
		6'-6"	8'-6"
8'-0" PANELS	36"	45° - 135°	54° - 126°
	45"	44° - 136°	52° - 128°
	54"	42° - 138°	51° - 129°
	AASHTO TYPE V AASHTO TYPE VI MODIFIED BULB TEES	31° - 149°	43° - 137°
4'-0" PANELS	36"	72° - 108°	76° - 104°
	45"	71° - 109°	76° - 104°
	54"	70° - 110°	75° - 105°
	AASHTO TYPE V AASHTO TYPE VI MODIFIED BULB TEES	61° - 119°	71° - 109°

NOTES TO DESIGNER:

\* SKEW LIMITS MAY BE INTERPOLATED FOR GIRDER SPACINGS BETWEEN 6'-6" AND 8'-6".

SPACINGS SHOWN ARE FOR REFERENCE. SPACINGS OVER 8'-6" SHOULD BE CHECKED FOR A MINIMUM PANEL WIDTH OF 2'-0" AND A MAXIMUM PANEL WIDTH OF EITHER 4'-0" OR 8'-0" DEPENDING ON PANEL SIZE.

SKEW LIMIT GUIDELINES

FOR PRECAST CONCRETE DECK PANELS

**FIGURE 6 - 9**

SKEW LIMITS			
	GIRDER SIZE	GIRDER SPACING *	
		1.98m	2.59m
2.44m PANELS	914mm	45° - 135°	54° - 126°
	1143mm	44° - 136°	52° - 128°
	1372mm	42° - 138°	51° - 129°
	AASHTO TYPE V AASHTO TYPE VI MODIFIED BULB TEES	31° - 149°	43° - 137°
1.22m PANELS	914mm	72° - 108°	76° - 104°
	1143mm	71° - 109°	76° - 104°
	1372mm	70° - 110°	75° - 105°
	AASHTO TYPE V AASHTO TYPE VI MODIFIED BULB TEES	61° - 119°	71° - 109°

NOTES TO DESIGNER:

\* SKEW LIMITS MAY BE INTERPOLATED FOR GIRDER SPACINGS BETWEEN 1.98m AND 2.59m.

SPACINGS SHOWN ARE FOR REFERENCE. SPACINGS OVER 2.59m SHOULD BE CHECKED FOR A MINIMUM PANEL WIDTH OF 610mm AND A MAXIMUM PANEL WIDTH OF EITHER 1.22m OR 2.44m DEPENDING ON PANEL SIZE.

SKEW LIMIT GUIDELINES

FOR PRECAST CONCRETE DECK PANELS

**FIGURE 6 - 9 M**