



STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION

JOSH STEIN  
GOVERNOR

DANIEL H. JOHNSON  
SECRETARY

MEMORANDUM TO: Project Engineers  
Project Design Engineers

FROM: D.N. Snoke, P.E.  
State Structures Engineer

DATE: June 9, 2026

SUBJECT: REVISION TO STANDARD DRAWINGS

At the request of the Construction Unit, the following Standard Drawings have been revised to facilitate accuracy and consistency of construction elevations:

| Standard No.        | Summary of Revision                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PCG1, PCG2,<br>PCG3 | <p>Revised the following plan note:</p> <p><i>The top surface of the girder shall be raked to a depth of <math>\frac{1}{4}</math>" except in the area between the stirrup and the edge of the girder.</i></p> <p>To:</p> <p><i>The top surface of the girder shall be raked to a depth of <math>\frac{1}{4}</math>", except for a <math>2\frac{1}{2}</math>" wide strip along the centerline of the girder and 1" wide strips along the edges of the top flange.</i></p> |
| PCG9                | <p>Revised the following plan note:</p> <p><i>The top surface of the girder, excluding the outside 4", shall be raked to a depth of <math>\frac{1}{4}</math>".</i></p> <p>To:</p> <p><i>The top surface of the girder shall be raked to a depth of <math>\frac{1}{4}</math>", except for a <math>2\frac{1}{2}</math>" wide strip along the centerline of the girder and 1" wide strips along the edges of the top flange.</i></p>                                        |

The Standard Drawings are available on both the network drive and the Structures Management Unit website.

Mailing Address:  
NC DEPARTMENT OF TRANSPORTATION  
STRUCTURES MANAGEMENT UNIT  
1581 MAIL SERVICE CENTER  
RALEIGH, NC 27699-1581

Telephone: 919-707-6400  
Fax: 919-250-4082  
Customer Service: 1-877-368-4968

Website: [ncdot.gov](http://ncdot.gov)

Location:  
1000 BIRCH RIDGE DRIVE  
RALEIGH, NC 27610

This policy is effective immediately.

DNS/NAP/AYG

Cc: G. Muchane, P.E.  
T.H. Carroll, P.E.  
K.M. Feltes, P.E.  
T.W. Whittington, P.E.  
Division Bridge Program Managers  
Regional Bridge Construction Engineers  
Area Construction Engineers