

[illegible]

## Field Operations Feedback

"... include sections of special sediment control fence outlets where long runs of silt fence are designed..."

*"... ensure plans are formatted and packaged properly with Title sheet, detail sheet, soil stabilization (matting) sheet, clearing and grubbing sheet, final grade sheet, and reforestation sheet all included in submittal..."*

"... include supporting calculations..."

"...suggest impervious dike, cofferdams, and turbidity curtains when footings or bulkheads are to be removed from existing stream or along stream bank. May be easiest to include as incidental to structure removal..."

"...overuse of PSRM is a concern. Its not the easiest product to grow vegetation through..."

## Field Operations Feedback

"...they have taken the wattle barrier BMP and ran with it. I suggest there be some restrictions on its use like situations where clearance under bridge makes silt fence posts difficult to install/remove ..."

*"...it would be beneficial to know what the drainage areas are for sediment basins. Adding some polygons on submitted topo maps would help us understand design approach..."*

"... I wish they would use a heavier line weight for EC devices. My eyes aren't what they once were and I'm having to use a magnifying glass at times..."

**in additional construction  
ts to shift large sediment basins  
under fill slopes so they can  
nd function during mass grading  
ns. It seems the majority of our  
problems occur when we remove basins  
prior to establishing permanent vegetation  
on slopes..."**

**"... sediment storage between  
Clearing/Grubbing and Final Grade  
Phase is an issue on Design Build  
Erosion Control Plans..."**

***"... my biggest concern is  
location of EC measures  
without consideration of  
permitted areas. Are EC  
designer and individual  
obtaining permits  
communicating?"***

## Field Operations Feedback

"...suggest wetland files be added to erosion control plan sheets to help show proximity of these areas to erosion control BMPS..."

"...can some type of SDO (storm discharge outfall) designation be listed with appropriate EC devices on plan sheet? It would help with NPDES documentation..."

"... careful with arbitrarily designing silt fence in wetland areas. It's unlikely to function properly if there is standing water in wetland..."


## NCDOT Erosion and Sediment Control Design Guidelines and Tools

- Low impact Bridge Design
- Reclamation Plan Submittals




## Low Impact Bridge Design

- EC plan sheets
- Erosion Control Plan and Permit Drawing
- Selecting the proper Erosion and Sediment Control BMP
- Including the proper Erosion and Sediment Control BMP quantity
- Including the proper Special Provisions



## EC PLAN SHEETS

**Title Sheet**





**Soil Stabilization**

STATE OF MISSISSIPPI DEPARTMENT OF TRANSPORTATION	
SOIL STABILIZATION STANDARD SHEET	
SECTION NO.	SECTION DESCRIPTION
1	1.000 TO 1.000
2	2.000 TO 2.000
3	3.000 TO 3.000
4	4.000 TO 4.000
5	5.000 TO 5.000
6	6.000 TO 6.000
7	7.000 TO 7.000
8	8.000 TO 8.000
9	9.000 TO 9.000
10	10.000 TO 10.000
11	11.000 TO 11.000
12	12.000 TO 12.000
13	13.000 TO 13.000
14	14.000 TO 14.000
15	15.000 TO 15.000
16	16.000 TO 16.000
17	17.000 TO 17.000
18	18.000 TO 18.000
19	19.000 TO 19.000
20	20.000 TO 20.000
21	21.000 TO 21.000
22	22.000 TO 22.000
23	23.000 TO 23.000
24	24.000 TO 24.000
25	25.000 TO 25.000
26	26.000 TO 26.000
27	27.000 TO 27.000
28	28.000 TO 28.000
29	29.000 TO 29.000
30	30.000 TO 30.000
31	31.000 TO 31.000
32	32.000 TO 32.000
33	33.000 TO 33.000
34	34.000 TO 34.000
35	35.000 TO 35.000
36	36.000 TO 36.000
37	37.000 TO 37.000
38	38.000 TO 38.000
39	39.000 TO 39.000
40	40.000 TO 40.000
41	41.000 TO 41.000
42	42.000 TO 42.000
43	43.000 TO 43.000
44	44.000 TO 44.000
45	45.000 TO 45.000
46	46.000 TO 46.000
47	47.000 TO 47.000
48	48.000 TO 48.000
49	49.000 TO 49.000
50	50.000 TO 50.000
51	51.000 TO 51.000
52	52.000 TO 52.000
53	53.000 TO 53.000
54	54.000 TO 54.000
55	55.000 TO 55.000
56	56.000 TO 56.000
57	57.000 TO 57.000
58	58.000 TO 58.000
59	59.000 TO 59.000
60	60.000 TO 60.000
61	61.000 TO 61.000
62	62.000 TO 62.000
63	63.000 TO 63.000
64	64.000 TO 64.000
65	65.000 TO 65.000
66	66.000 TO 66.000
67	67.000 TO 67.000
68	68.000 TO 68.000
69	69.000 TO 69.000
70	70.000 TO 70.000
71	71.000 TO 71.000
72	72.000 TO 72.000
73	73.000 TO 73.000
74	74.000 TO 74.000
75	75.000 TO 75.000
76	76.000 TO 76.000
77	77.000 TO 77.000
78	78.000 TO 78.000
79	79.000 TO 79.000
80	80.000 TO 80.000
81	81.000 TO 81.000
82	82.000 TO 82.000
83	83.000 TO 83.000
84	84.000 TO 84.000
85	85.000 TO 85.000
86	86.000 TO 86.000
87	87.000 TO 87.000
88	88.000 TO 88.000
89	89.000 TO 89.000
90	90.000 TO 90.000
91	91.000 TO 91.000
92	92.000 TO 92.000
93	93.000 TO 93.000
94	94.000 TO 94.000
95	95.000 TO 95.000
96	96.000 TO 96.000
97	97.000 TO 97.000
98	98.000 TO 98.000
99	99.000 TO 99.000
100	100.000 TO 100.000

**Soil Stabilization Time Frame**

STATE OF MISSISSIPPI DEPARTMENT OF TRANSPORTATION	
SOIL STABILIZATION TIME FRAME	
DATE	DESCRIPTION
1/1/2013	1.000 TO 1.000
2/1/2013	2.000 TO 2.000
3/1/2013	3.000 TO 3.000
4/1/2013	4.000 TO 4.000
5/1/2013	5.000 TO 5.000
6/1/2013	6.000 TO 6.000
7/1/2013	7.000 TO 7.000
8/1/2013	8.000 TO 8.000
9/1/2013	9.000 TO 9.000
10/1/2013	10.000 TO 10.000
11/1/2013	11.000 TO 11.000
12/1/2013	12.000 TO 12.000
1/1/2014	13.000 TO 13.000
2/1/2014	14.000 TO 14.000
3/1/2014	15.000 TO 15.000
4/1/2014	16.000 TO 16.000
5/1/2014	17.000 TO 17.000
6/1/2014	18.000 TO 18.000
7/1/2014	19.000 TO 19.000
8/1/2014	20.000 TO 20.000
9/1/2014	21.000 TO 21.000
10/1/2014	22.000 TO 22.000
11/1/2014	23.000 TO 23.000
12/1/2014	24.000 TO 24.000
1/1/2015	25.000 TO 25.000
2/1/2015	26.000 TO 26.000
3/1/2015	27.000 TO 27.000
4/1/2015	28.000 TO 28.000
5/1/2015	29.000 TO 29.000
6/1/2015	30.000 TO 30.000
7/1/2015	31.000 TO 31.000
8/1/2015	32.000 TO 32.000
9/1/2015	33.000 TO 33.000
10/1/2015	34.000 TO 34.000
11/1/2015	35.000 TO 35.000
12/1/2015	36.000 TO 36.000
1/1/2016	37.000 TO 37.000
2/1/2016	38.000 TO 38.000
3/1/2016	39.000 TO 39.000
4/1/2016	40.000 TO 40.000
5/1/2016	41.000 TO 41.000
6/1/2016	42.000 TO 42.000
7/1/2016	43.000 TO 43.000
8/1/2016	44.000 TO 44.000
9/1/2016	45.000 TO 45.000
10/1/2016	46.000 TO 46.000
11/1/2016	47.000 TO 47.000
12/1/2016	48.000 TO 48.000
1/1/2017	49.000 TO 49.000
2/1/2017	50.000 TO 50.000
3/1/2017	51.000 TO 51.000
4/1/2017	52.000 TO 52.000
5/1/2017	53.000 TO 53.000
6/1/2017	54.000 TO 54.000
7/1/2017	55.000 TO 55.000
8/1/2017	56.000 TO 56.000
9/1/2017	57.000 TO 57.000
10/1/2017	58.000 TO 58.000
11/1/2017	59.000 TO 59.000
12/1/2017	60.000 TO 60.000
1/1/2018	61.000 TO 61.000
2/1/2018	62.000 TO 62.000
3/1/2018	63.000 TO 63.000
4/1/2018	64.000 TO 64.000
5/1/2018	65.000 TO 65.000
6/1/2018	66.000 TO 66.000
7/1/2018	67.000 TO 67.000
8/1/2018	68.000 TO 68.000
9/1/2018	69.000 TO 69.000
10/1/2018	70.000 TO 70.000
11/1/2018	71.000 TO 71.000
12/1/2018	72.000 TO 72.000
1/1/2019	73.000 TO 73.000
2/1/2019	74.000 TO 74.000
3/1/2019	75.000 TO 75.000
4/1/2019	76.000 TO 76.000
5/1/2019	77.000 TO 77.000
6/1/2019	78.000 TO 78.000
7/1/2019	79.000 TO 79.000
8/1/2019	80.000 TO 80.000
9/1/2019	81.000 TO 81.000
10/1/2019	82.000 TO 82.000
11/1/2019	83.000 TO 83.000
12/1/2019	84.000 TO 84.000
1/1/2020	85.000 TO 85.000
2/1/2020	86.000 TO 86.000
3/1/2020	87.000 TO 87.000
4/1/2020	88.000 TO 88.000
5/1/2020	89.000 TO 89.000
6/1/2020	90.000 TO 90.000
7/1/2020	91.000 TO 91.000
8/1/2020	92.000 TO 92.000
9/1/2020	93.000 TO 93.000
10/1/2020	94.000 TO 94.000
11/1/2020	95.000 TO 95.000
12/1/2020	96.000 TO 96.000
1/1/2021	97.000 TO 97.000
2/1/2021	98.000 TO 98.000
3/1/2021	99.000 TO 99.000
4/1/2021	100.000 TO 100.000

**BMP Details**




**EC Plan Sheet(s)**

## Erosion Control Plan Design in Permitted Areas

Mechanized Clearing - allows soil inversion associated with removal of trees/stumps, but does NOT allow excavation or fill. Placement of Erosion and Sediment Control measures in Mechanized Clearing zone is considered fill (temporary) and should be accounted for.




Hand Clearing - NO soil inversion associated with removal of trees allowed. Stumps are not authorized for removal. Excavation and/or Fill are not authorized in Hand Clearing zones. Placement of Erosion and Sediment Control measures in Hand Clearing zones is considered fill (temporary) and will need accounted for.



## Erosion Control Plan Design in Permitted Areas

**Riparian Buffer Zones** – Permit needed for impacts to vegetation, any excavation or fill activities, and placement of temporary Erosion and Sediment Control devices. Permanent stabilization measures like use of Rip/Rap should also be accounted for.



## Selecting the Proper Erosion and Sediment Control BMP

### Perimeter BMPs

- Silt fence
  - Effective for most any slope but does require drainage outlet points.
  - Should be offset from toe of slope to allow for construction of fill and maintenance (check permit).
  - Not effective in standing water (wetlands).



## Selecting the proper Erosion and Sediment Control BMP

### Perimeter BMPs

- Wattle Barrier (Coir Fiber/Excelsior)

Effective for short slopes with limited drainage area. Doesn't require drainage outlet points.

Should be offset from toe of slope to allow for construction of fill and maintenance (check permit).

Not Effective in standing water (wetlands).

Less removal effort required compared to other BMPs.



## Selecting the proper Erosion and Sediment Control BMP

### Perimeter BMPs

- Special Sediment Control Fence

Effective for all slopes. Doesn't require drainage outlet points.

Should be offset from toe of slope to allow for construction of fill and maintenance (check permit).

Somewhat effective in standing water (wetlands).

Stringent removal effort needed compared to other BMPs. Can be problematic *in and around jurisdictional areas.*





## Selecting the proper Erosion and Sediment Control BMP

### Perimeter BMPs

- Turbidity Curtain  
Required on most projects involving 401 permits where piles/shafts anticipated in jurisdictional water.  
Beneficial when earth disturbing activities expected on stream banks.



## Selecting the proper Erosion and Sediment Control BMP

### Rolled Erosion Control Products (Matting)

Recommend including a quantity on all projects.  
Note on EC plans identifying slopes is adequate.  
Coir Fiber Mat should be used for stream banks and flood plain.  
Temporary Erosion Control Matting (Excelsior) for most slopes.  
Permanent Soil Reinforcement Matting or Turf Reinforcement Matting for ditches with steep grade (4% to 5%).



## **Erosion and Sediment Control BMP Quantities**

### Wattles

- 10 foot length increments
- Recommend minimum of 50 foot (5 wattles) be included on all low impact bridge projects

### Temporary Slope Drains

- Recommend a minimum quantity when earth disturbance expected on fill slopes
- Consider slope height

### Special Stilling Basin

- Necessary for any project with drilled shafts
- Recommend minimum quantity of 2

### Coir Fiber Mat

- Recommend minimum quantity be included on all low impact bridge projects with expected work adjacent to jurisdictional waters
- Consider area under structure
- Only type of matting recommended for stream bank stabilization

## **Erosion and Sediment Control Special Provisions**

- Erosion and Sediment Control/Storm Water Certification (NPDES)
- Permanent Vegetation Establishment and Related Intermediate Completion Time
- Shoulder and Fill Slope Material (pH/PI)
- Shoulder and Slope Borrow



## Reclamation Plans

- Environmental Evaluation
- Erosion Control Plan
- Dewatering Information



## Reclamation Plans

### Environmental Evaluation


- Experienced Environmental Consultant
- Identify Jurisdictional Features and Protected Species
- Identify Historical Properties



## Reclamation Plans

### Erosion Control Plan


- Level III B EC/SW Certification #
- Include Calculations
- Provide Cross Section
- Locate Construction Access
- Locate Top Soil Piles




## Reclamation Plans

### Dewatering Information

- CCPCUA (Central Coastal Plain Capacity Use)
- Skaggs Method
- Dewatering Basin



## Reclamation Plans



North Carolina Department of Transportation  
**Roadside Environmental Unit**  
Field Operations

HOME CONTACT SEARCH

NC DOT  
NC DOH  
NC GOV

IMPORTANT DOWNLOADS | GENERAL INFORMATION | KNOW BEFORE YOU MOW | LINKS

**FIELD OPERATIONS**

HOME > IMPORTANT DOWNLOADS

**IMPORTANT DOWNLOADS**

**RECLAMATION PLAN PROCEDURES FOR:**

[OPERATIONS Projects](#) (534 KB) - Interactive Form

[CONTRACT Projects](#) (564 KB) - Interactive Form

**RECLAMATION PLAN PROCEDURES FOR:**

[OPERATIONS Projects](#) (534 KB) - Interactive Form

[CONTRACT Projects](#) (564 KB) - Interactive Form

**CENTRAL COASTAL PLAIN CAPACITY USE AREA:**

[Map](#) (186 KB)

[Spreadsheet](#) (28 KB)

[http://www.ncdot.gov/doh/operations/dp\\_chief\\_eng/roadside/fieldops/downloads/](http://www.ncdot.gov/doh/operations/dp_chief_eng/roadside/fieldops/downloads/)

## Summary

- EC plan submittals for review should include all related plan sheets
- Erosion Control Plans and Permit drawings should be compared to ensure perimeter BMPs can be installed as well as permanent stabilization along jurisdictional areas
- Select the proper BMP for perimeter containment and stabilization
- Include proper Pay Items and adequate Quantities
- Include necessary Special Provisions
- Follow Reclamation Plan Guidelines related to Waste/Borrow/Staging Areas off right of way