



Signed by:
Matthew V. Springer
BC60F6E8B584403...
04-21-26

TYPE 3 FLEXIBLE GROUND MOUNTED OBJECT MARKERS

(4-21-26)

Description

Furnish and install type 3 flexible ground mounted object markers. Affix flexible ground mounted object marker to a base capable of restoring the marker to the vertical position if struck by a vehicle.

Material

Use type 3 flexible ground mounted object markers that are on the NCDOT APL.

The flexible ground mounted object marker shall be composed of UV-stabilized high impact plastic and be a minimum of 12 inches wide and 48 inches high. The flexible ground mounted object marker shall consist of a retroreflective sheeting, flat panel, post and permanent base. Attach the post to the base with a flexible mount or similar device capable of restoring the marker to the vertical position if struck by a vehicle.

The flexible ground mounted object marker shall accommodate a minimum of 12 inches x 36 inches of Grade C high intensity retroreflective sheeting that meets the applicable requirements of Section 1092 of the *Standard Specifications*. The retroreflective sheeting shall meet the color and stripe patterns of a Type 3 Object Marker in accordance with MUTCD and the applicable requirements of Section 1088 of the *Standard Specifications*.

Construction

Install type 3 flexible ground mounted object markers in accordance with manufacturer's specifications.

Measurement and Payment

Type 3 Flexible Ground Mounted Object Markers will be measured and paid as the actual number of object markers satisfactorily placed and accepted by the Engineer.

Payment will be made under:

Pay Item
Type 3 Flexible Ground Mounted Object Markers

Pay Unit
Each