



YIELD LINES PAVEMENT MARKING:

(1-15-24)(Rev. 9-17-24)

Description

Install yield lines in accordance with this special provision, Section 1205 of the *Standard Specifications* and as directed by the Engineer.

Materials

Refer to Division 10 of the Standard Specifications.

Item	Section
Pavement Markings	1087

The material for yield line pavement markings shall be thermoplastic, polyurea, type III cold applied plastic, or heated-in-place thermoplastic. Paint may be used for temporary yield line pavement markings.

Application

Refer to Section 1205 of the *Standard Specifications* and refer to Division 12 of the *Roadway Standard Drawings* on application of products used for yield lines. Yield lines shall be a row of solid white isosceles triangles with 3 to 12 inches between each one, 12 to 24 inches in width, with a height 1.5 times the width. Yield lines shall point towards traffic, and they shall be placed at least 4 feet before the nearest controlled crosswalk. For unsignalized midblock crosswalks, yield lines shall be placed with the Yield Here to Pedestrians sign located 20 to 50 feet in advance of the crosswalk. Yield lines are not symbols or characters.

Measurement and Payment

Yield Line	_ Pavement Marking,	", <i>mils</i> (for the	moplastic, polyure	ea and heated
in-place thermoplastic	e material), Yield Line	Pavement Marking,	<i>Type III</i> (") (fo	r Type 3 colo
applied plastic mater	ial), or <i>Yield Line Pa</i>	ivement Marking, _	_" (for paint mat	terial) will be
measured and paid as	the actual number of	linear feet of paven	nent marking lines	satisfactorily

placed and accepted by the Engineer. The quantity	of lines will be th	e summation	of the linear fee	et
of solid line measured end-to-end of the line.				

Payment will be made under:

Pay Item		Pay Unit
Yield Line	Pavement Marking,",mils	Linear Feet
Yield Line Cold Applie	ed Plastic Pavement Marking, Type III (")	Linear Feet
Yield Line Paint Paven	nent Marking,"	Linear Feet