

Spacing Factor is 1 unless specified otherwise

Spacing Factor is 1 unless specified otherwise

Spacing Factor is 1 unless specified otherwise

Spacing Factor is 1 unless specified otherwise

Stephen T. Kistrowski

[illegible]

1. Legend and border shall be direct applied Type III reflective sheeting.
2. Legend and border shall be direct applied non-reflective sheeting.
3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.
4. Background shall be Type III reflective sheeting.
5. Background shall be Type I reflective sheeting.
6. Center arrow(s) vertically on sign.
7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

LETTER POSITIONS

[illegible]

Spacing Factor is 1 unless specified otherwise

Spacing Factor is 1 unless specified otherwise

Spacing Factor is 1 unless specified otherwise

Spacing Factor is 1 unless specified otherwise

Stephen T. Kestrow


DIV: STATEWIDE

[illegible]

RADII: 6"

MAT'L: 0.125" (3.2 mm) ALUMINUM

1. Legend and border shall be direct applied Type III reflective sheeting.
2. Legend and border shall be direct applied non-reflective sheeting.
3. Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.
4. Background shall be Type III reflective sheeting.
5. Background shall be Type I reflective sheeting.
6. Center arrow(s) vertically on sign.
7. Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:



Letter spacings are to start of next letter

[illegible]

Spacing Factor is 1 unless specified otherwise