



**SIGN NUMBER:** SPO5001

**BACKG COLOR:** Green

**DESIGN BY:** BSESSOMS

**DATE:** Jan 05,2005

**CHECKED BY:**

**TYPE:** D

**COPY COLOR:** White

**TEPPL TOPIC:** W-09

**DIV:** STATEWIDE

*[Handwritten Signature]*

**QUANTITY:** 1

SYMBOL	X	Y	WID	HT

**SIGN WIDTH:** 3'-0"

**HEIGHT:** 2'-6"

**TOTAL AREA:** 7.5 Sq.Ft.

**BORDER TYPE:** FLUSH

**RECESS:** 0"

**WIDTH:** 0.5"

**RADII:** 3"

**MAT'L:** 0.080" (2.0 mm) ALUMINUM

**NO. Z BARS:**

**LENGTH:**

**USE NOTES:** 1,4

- Legend and border shall be direct applied Type III reflective sheeting.
- Legend and border shall be direct applied non-reflective sheeting.
- Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.
- Background shall be Type III reflective sheeting.
- Background shall be Type I reflective sheeting.
- Center arrow(s) vertically on sign.
- Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:



**LETTER POSITIONS**

**Letter spacings are to start of next letter**

**Series/Size  
Text Length**

	W	A	T	E	R		S	U	P	P	L	Y														
2.6	2.8	2.7	2.4	2.4	2	3	2.7	2.7	2.7	2.7	2	2.5	2.6													D3 30.8
	A	R	E	A																						
12.7	3.1	2.7	2.2	2.5	12.7																					D3 10.5
	N	E	X	T		2			M	I	L	E	S													
3.8	2.7	2.4	2.4	1.8	3	2	3	3	1.2	2.4	2.4	2	3.8													D3 28.4
	S	P	I	L	L		R	E	S	P	O	N	S	E												
3.4	2.3	2.3	1.1	2	1.5	3	2.3	2	2.3	2.1	2.4	2.3	2.3	1.5	3.4											C3 29.2
	9	1	1																							
15.9	2.3	1.2	0.6	15.9																						C3 4.1

Spacing Factor is 1 unless specified otherwise



**SIGN NUMBER:** SPO5002      **BACKG COLOR:** Green  
**TYPE:** D      **COPY COLOR:** White  
**QUANTITY:** 1

SYMBOL	X	Y	WID	HT

**SIGN WIDTH:** 3'-0"  
**HEIGHT:** 2'-0"  
**TOTAL AREA:** 6.0 Sq.Ft.

**BORDER TYPE:** FLUSH  
**RECESS:** 0"  
**WIDTH:** 0.5"  
**RADII:** 3"

**NO. Z BARS:**      **MAT'L:** 0.080" (2.0 mm) ALUMINUM  
**LENGTH:**      **LENGTH:**

**DESIGN BY:** BSESSOMS      **DATE:** Jan 05,2005      **CHECKED BY:** *[Signature]*  
**TEPPL TOPIC:** W-09      **DIV:** STATEWIDE



- USE NOTES:** 1,4
- Legend and border shall be direct applied Type III reflective sheeting.
  - Legend and border shall be direct applied non-reflective sheeting.
  - Shields shall be Type III reflective sheeting on 0.032" (0.8mm) aluminum and demountable.
  - Background shall be Type III reflective sheeting.
  - Background shall be Type I reflective sheeting.
  - Center arrow(s) vertically on sign.
  - Bottom panel shall be yellow Type III sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is:

**LETTER POSITIONS**

Letter spacings are to start of next letter

															Series/Size Text Length							
		W	A	T	E	R		S	U	P	P	L	Y									D3
2.6	2.8	2.7	2.4	2.4	2	3	2.7	2.7	2.7	2.7	2	2.5	2.6									30.8
		A	R	E	A																	D3
12.7	3.1	2.7	2.2	2.5	12.7																	10.5
		S	P	I	L	L		R	E	S	P	O	N	S	E							C3
3.4	2.3	2.3	1.1	2	1.5	3	2.3	2	2.3	2.1	2.4	2.3	2.3	1.5	3.4							29.3
		9	1	1																		C3
15.9	2.3	1.2	0.6	15.9																		4.1