

NCDOT Standard for Logo Mileage Panels Mounted under Business Panels on Ramp Logo Signs

THIS MILEAGE PANEL DESIGN STANDARD SHALL BE USED ON LOGO RAMP SIGNS. THE FOLLOWING DESIGN REQUIREMENTS SHALL APPLY:

- 1. PANEL SHALL BE .032" ALUMINUM**
- 2. USE MINIMUM GRADE C SHEETING**
- 3. USE 6"C WHITE NUMBERS**
- 4. USE 9" X 6" STANDARD WHITE ARROW;
EXCEPT MODIFY TO 6.5" X 6" FOR THROUGH (UP) ARROW**
- 5. PANEL SHALL HAVE BLUE BACKGROUND**
- 6. PLACE LEGEND AND ARROW .5" FROM EACH END OF PANEL**
- 7. PLACE VERTICAL ARROW .25" FROM TOP AND BOTTOM OF PANEL**
- 8. DECIMAL SHALL BE 1.25" DIAMETER WITH 1" SPACING LEFT AND RIGHT OF DECIMAL, EXCEPT WHEN USING NUMBER 1, AT WHICH TIME SPACING SHALL BE 1.5" LEFT OR RIGHT OF DECIMAL
(SEE * ON EXAMPLE DESIGNS)**
- 9. MILEAGE SHALL BE SHOWN TO THE NEAREST TENTH**

EXAMPLE DESIGNS:

