

Facility	Median or Outside shoulder	Median Width	Offset from Travel Lane to Centerline of Support	Guardrail Required	Supports location
			Greater or equal to 40'	NO	Centerline of support should be located a distance of 4' preferred, 3' minimum from the center of the ditch bottom.
		Greater or equal to 70'			
	Median		Less than 40'	YES	Centerline of support should be located in <b>center of the median</b> . Do not consider the location of the ditch.
Freeway or posted speed greater than 55 mph		Median width of less than 70'	Less than 40'	YES	Centerline of support should be located in <b>center of the median</b> . Do not consider the location of the ditch.
			Greater or equal to 40'	NO	Centerline of support should be located a distance of 4' preferred, 3' minimum from the center of the ditch bottom.
	Outside Shoulder				
			Less than 40'	YES	Centerline of support should be located a distance of 4' preferred, 3' minimum from the center of the ditch bottom.
			Greater or equal to 32'	NO	Centerline of support should be located a distance of 4' preferred, 3' minimum from the center of the ditch bottom.
	Median				
Expressway with posted speed limits of 55 mph or less			Less than 32'	YES	Centerline of support should be located in <b>center of the median</b> . Do not consider the location of the ditch.
			Greater or equal to 32'	NO	Centerline of support should be located a distance of 4' preferred, 3' minimum from the center of the ditch bottom.
	Outside Shoulder				
			Less than 32'	YES	Centerline of support should be located a distance of 4' preferred, 3' minimum from the center of the ditch bottom.